

## **TEST CERTIFICATE**

This is to certify that the nominated size and quality of the following SLR product has been inspected and tested with following results.

 $\epsilon$ 

Page 1

**Customer Sold To:** 

HESNZ 3 Heb Place

Takanini, Auckland, New Zealand

Order:	4076	Test Standard:	EN1677
Invoice:	21697	Certificate No:	SLR19964
Material:	G80		
Date:	3/09/2018	Batch:	18-2
Brand	SLR	Colour:	Yellow

ltem	Quantity (pcs)	Test Quantity (pcs)	Working Load Limit (ton) / WLL	Standard Breakage Force (ton) / BF	Fact Breakage Force (ton) / BF
SLR-74 CONNECTING LINK 6-8	900	5	1.12T	4.48T	4.52T、4.54T、4.5T、4.58T、4.6T
SLR-74 CONNECTING LINK 7/8-8	480	3	2Т	8Т	8.13T、8.07T、8.05T
SLR-74 CONNECTING LINK 13-8	150	3	5.3T	21.2T	21.26T、21.34T、21.5T
SLR-74 CONNECTING LINK 16-8	100	2	8T	32T	32.36T、32.17T
SLR-12 CLEVIS SLING HOOK 7/8-8	180	3	2T	8T	8.12T、8.07T、8.04T
SLR-344 FORGED D RING 1T	200	3	1.12T	4.48T	4.56T、4.52T、4.6T
SLR-344 FORGED D RING 2T	200	3	2T	8T	8.05T、8.1T、8.17T
SLR-344 FORGED D RING 3T	90	2	3.15T	12.6T	13.06T、12.8T
SLR-344 FORGED D RING 5T	300	3	5.3T	21.2T	21.25T、21.32T、21.4T
SLR-344 FORGED D RING 15T	8	1	15T	60T	60.3T
SLR-633 CONTAINER HOOK LEFT TYPE 12.5T	40	. 1	12.5T	, 50Т	50.26T
SLR-633 CONTAINER HOOK RIGHT TYPE 12.5T	40	1	12.5T	50T	50.18T
SLR-106 WELDED HOOK LIGHT TYPE 3.2T	30	1	3.2T	16T	16.2T
SLR-1001 CONNECTING LINK 10-10	50	1	4T	16T	16.13T
SLR-1001 CONNECTING LINK 13-10	180	3	6.7T	26.8T	26.87T、27.1T、26.93T
SLR-1001 CONNECTING LINK 16-10	160	3	10T	40T	40.15T、40.27T、40.2T
SLR-1011 MASTER LINK NO FLAT 22-10	50	1	7.6T	30.4T	30.54T
SLR-1011 MASTER LINK NO FLAT 26-10	200	., 3	10T	, 40T	40.32T、40.16T、40.2T
SLR-887 ANCHOR SHACKLE 6-8	1000	5	1.12T	4.48T	4.57T、4.52T、4.5T、4.54T、4.6T
SLR-887 ANCHOR SHACKLE 8-8	2000	6	2Т	8T	8.2T、8.15T、8.1T、8.12T、8.04T、8.07T
SLR-887 ANCHOR SHACKLE 10-8	75	2	3.15T	12.6T	12.8T、12.92T
SLR-887 ANCHOR SHACKLE 13-8	300	3	8T	32T	32.17T、32.2T、32.13T

